



Elektra[®]

ZAKŁADY ELEKTROMECHANICZNE S.I.
ul. Przasnyska 6A
01-756 Warszawa

Tel.(0-22) 4316-171(172) Fax. (0-22) 639 73 45
www.zeelektra.com.pl
email: handel@zeelektra.com.pl

We have implemented 9001

INSTRUCTION FOR INSTALATION AND USE DIRECTIONAL LED LAMP type MS6BS

GENERAL DESCRIPTION

Directional LED lamp MS6BS forms an units of the warning equipment of special and privileged vehicles in road movement.

FEATURES:

- Super low profile for discreet mounting.
- Multi-Voltage Input 11-30VDC.
- Built-in 5 selectable flash patterns.
- LEDs rated to 100.000 hours of operation.
- Non - volatile memory recalls last flash pattern used at power up.
- Multiple units are synchronizable and can flash simultaneously or alternately.
- Reverse polarity protection.
- Weatherproof and vibration resistant design for external or internal use.

SPECIFICATION:

Meets: SAE, R65, e13

Bulb: 1W LED x 6 pcs.

Warning Patterns: 5 Flash Patterns

Operating Voltage: 10,8 - 30VDC

Average Current 0,4A@12,8VDC; 0,22A@24VDC

Average Power: 5,5W (varies with flash pattern)

Max. Current: 0,8A@ 12,8V; 0,44A@ 24VDC

Max Power: 10,5W.

Wires: Red-Vcc: 150mm

Black-GND: 150mm

Yellow - Flash Pattern&Sync.: 150mm

Fuse Recommended: 3A

Multi Unit Synchronization: Over 15 units .

Available in: red,blue,amber,white.

DIMENSIONS:

(mm)

